

(11)Publication number:

11-063253

(43)Date of publication of application: 05.03.1999

(51)Int.CI.

F16K 7/16 F16K 27/00 F16L 23/026 F16L 23/024 F16L 23/028

(21)Application number: 09-224522

(71)Applicant: NIPPON DAIYABARUBU KK

(22)Date of filing:

21.08.1997


(72)Inventor: OMURA SHOZO

(54) DIAPHRAGM VALVE

(57)Abstract:

PROBLEM TO BE SOLVED: To facilitate the manufacture of a resinous diaphragm valve body.

SOLUTION: A diaphragm valve body comprises a resinous solid member 10 having a passage 11 and a valve sealing part 12, flange couplings 30 formed independently of the solid member so as to fit around the passage inlet and outlet ends of the solid member, and a fixing means to fix the couplings to the solid member. The fixing means is typically a fixing member 40 adapted to be interposed between the couplings on both the sides and also fixed to the couplings and the solid member. The valve body is arbitrarily mounted with spacers 20 each divisible into a plurality of circumferential sections at its positions between the solid member and the couplings. Each of the spacer sections has the first locking part to be locked on the solid member and the second locking part to lock the coupling; when fitted on the coupling, the first locking part is secured on the solid member while the second locking part locks the coupling in place. This solid member is cut out of, for example, polytetrafluoroethylene(PTFE) material.



LEGAL STATUS

[Date of request for examination]

02.07.2004

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]

[Date of extinction of right]